

## Lowering your R&J Machine Lift dock !



### Step 1

Start of by untying of your guides ropes from your tree or eyhook. You can let them go loose as you will wrap them up later.



### Step 2

Begin to crank your winch counter-clockwise to lower your dock down.



### Step 3

Disconnect your winch cable, and wrap it up with your winch. Pull out the bolt at the bottom of your winch stand, and store it for the season!

### Step 4

If you have an "L" section, you will have to remove those cables from the tower and wrap the up in their respective corners. If not, you can pull all of your cables back and tape them to the tower.



### Step 5

Once, your tower is down flat and your cables are pulled up and out of the water, you can start decking. Your first board will have 5 boards, and the rest will have 4. Our panels are interchangeable, if you would like to change a cleat position! Finally, putting on your trim strips! It's often easier if you lay them out prior to starting!



### Step 6

Now you can comfortably walk out, and retrieve your guide ropes. You can add your ladder or other accessories.



## ~Tips~

### Putting on your trim

Use a number 3 phillips screw driver to remove the trim bolts.

**Do not use power tools.**

**\*\*Make sure your tower sits down flush, so that your decking will be able to sit over top\*\***



### Installer tip !

Before disconnecting your cables, now is a good time to make sure your dock is level, because you can use your winch to your advantage.

**Call us any time, we are happy to help!**

*If you have any questions, or are stuck, feel free to give us a call!*

